



# Damage Investigation of Surroundings of the Seismic Stations in the 2008 Iwate-Miyagi Nairiku Earthquake and Correspondence of Damage to Buildings with Strong Ground Motions

SAKAI Yuki<sup>1</sup>, AOI Atsushi<sup>2</sup>, ARAI Kensuke<sup>3</sup> and SUZUKI Tatsuya<sup>4</sup>

1 Member, Professor, University of Tsukuba, Graduate School of Systems and Information Eng., Dr. Eng., sakai@kz.tsukuba.ac.jp

2 Member, Former Graduate Student, University of Tsukuba, Graduate School of Systems and Information Eng., aoiusagi0129@hotmail.co.jp

3 Student Member, Graduate Student, University of Tsukuba, Graduate School of Systems and Information Eng., e0511266@edu.esys.tsukuba.ac.jp

4 Student Member, Graduate Student, University of Tsukuba, Graduate School of Systems and Information Eng., e0511348@edu.esys.tsukuba.ac.jp

**ABSTRACT:** We carried out damage investigation around the seismic stations where high JMA seismic intensity scales were recorded in the 2008 Iwate-Miyagi-Nairiku Earthquake. We found some minor damage such as small cracks in the wall or damaged roofs, but heavy damage to buildings was not found around all the seismic stations. We investigated the correspondence of strong ground motions with damage to buildings. Very short period below 0.5 sec. was dominated in most strong ground motions and the 1-2 sec. response which has close relationship with heavy damage to buildings was small, therefore, heavy damage to buildings was not found in spite of high JMA seismic intensity scale.

**Key Words:** The 2008 Iwate-Miyagi-Nairiku Earthquake, earthquake damage investigation, strong ground motion characteristics, JMA seismic intensity scale, seismic station